

Tornado

2" point source speaker carved from aluminum



Restaurants and Cafes



Hotels and Resorts



Retail



Museums and Exhibitions



Yachting



Theme Parks



Tornado-KT2 | WALL MOUNT

General

Type	Point source
Transducers	2" neodymium magnet woofer
Frequency Response ⁽¹⁾	150 Hz – 18 kHz (-6 dB)
Max SPL ⁽²⁾	107 dB (peak)
Rated Power	18 W
Coverage	V. 90° H. 90°
Connectors	4PIN euroblock connector (included)
Nominal Impedance	8 Ω / 32 Ω selectable 70V version avail. upon request

Handling & Finishes

Dimensions (WxHxD) ⁽¹⁰⁾	74 x 74 x 118 mm (2.91 x 2.91 x 4.65 in)
Weight	0.6 kg (1.32 lb)
Material	Aluminum
Colors	Black, White, Custom RAL
IP Rating	IP65
EN54-24 ⁽⁴⁾	EN 54-24:2008 compliant



Tornado-KT2C | CEILING MOUNT

General

Type	Point source
Transducers	2" neodymium magnet woofer
Frequency Response ⁽¹⁾	150 Hz – 18 kHz (-6 dB)
Max SPL ⁽²⁾	107 dB (peak)
Rated Power	18 W
Coverage	V. 90° H. 90°
Connectors	4PIN euroblock connector (included)
Nominal Impedance	8 Ω / 32 Ω selectable 70V version avail. upon request

Dimensions (WxHxD) ⁽¹⁰⁾	74 x 74 x 118 mm (2.91 x 2.91 x 4.65 in)
Weight	0.6 kg (1.32 lb)
Material	Aluminum
Colors	Black, White, Custom RAL
IP Rating	IP20
EN 54-24:2008 compliant	EN 54-24:2008 compliant



Dragon-KX12

General

Type	Point source
Transducers	Coaxial 12" woofer + 2.4" compression driver
Frequency Response ⁽¹⁾	120 Hz – 19 kHz (-6 dB)
Max SPL ⁽²⁾	133 dB (peak)
Rated Power	1200 W
Coverage	User sel. V./H. 30°/100° 100°/30°
Connectors	SpeakOn NL4 1+ 1- (signal); 2+ 2- (through)
Nominal Impedance	8 Ω

Handling & Finishes

Dimensions (WxHxD)	340 x 320 x 201 mm (13.4 x 12.6 x 7.9 in)
Weight	12.2 kg (26.89 lb)
Material	Stainless Steel
Colors	Black, White, Custom RAL
IP Rating	IP21

Dragon

Compact passive 12" coaxial stainless steel array element



Large Congregations



Stadiums and Sport Venues



Nightclubs and Lounges



Broadcast and Studios



Theme Parks



Turtle-KRM33P

General

Type	-
Transducers	3 x 3.15" neodymium magnet woofer 1 x 6" passive radiator
Frequency Response ⁽¹⁾	70 Hz – 20 kHz (-6 dB)
Max SPL ⁽²⁾	121 dB (peak)
Rated Power	300 W
Coverage	V. 90° H. 30° - 70° selectable
Connectors	SpeakOn NL4 1+ 1- (signal); 2+ 2- (through)
Nominal Impedance	8 Ω
Amp Module	
Output Power	

Handling & Finishes

Dimensions (WxHxD)	266 x 103 x 302 mm (10.5 x 4.1 x 11.9 in)
Weight	5.2 kg (11.59 lb)
Material	Stainless Steel
Colors	Black, White, Custom RAL
IP Rating	IP64

Turtle-KRM33

General

Type	Point source
Transducers	3 x 3.15" neodymium magnet woofer 1 x 6" passive radiator
Frequency Response ⁽¹⁾	70 Hz – 20 kHz (-6 dB)
Max SPL ⁽²⁾	121 dB (peak)
Rated Power	-
Coverage	V. 90° H. 30° - 70° selectable
Connectors	SpeakOn NL4 1+ 1- (signal); 2+ 2- (through)
Nominal Impedance	8 Ω
Amp Module	2 ch. switch-mode, class D
Output Power	2 x 125 W @ 4 Ω

Dimensions (WxHxD)	266 x 103 x 302 mm (10.5 x 4.1 x 11.9 in)
Weight	5.2 kg (11.59 lb)
Material	Stainless Steel
Colors	Black, White, Custom RAL
IP Rating	IP40

Turtle

Low-profile, variable coverage stainless steel speaker



Theaters



Auditoriums and Concert Halls



Houses of Worship



Broadcast and Studios



Boardrooms and Conference Rooms